









The AK612 is a high-performance passive speaker built for professional sound applications. It features a robust, premium-grade birch plywood cabinet with a durable premium paint finish, ensuring long-lasting protection against wear and tear. Designed for versatility, it excels in live sound, installations, and portable PA systems.


Key Specifications:

- LF Driver: 12-inch LF driver with a 75mm voice coil, providing powerful and responsive bass.
- HF Driver: 1-inch HF driver with a 44mm voice coil, delivering clear and accurate highs.
- Power Rating: 500W RMS, ensuring consistent output for demanding audio environments.
- Maximum SPL: Produces up to 130 dB, making it suitable for large venues and high-volume settings.
- Durable Construction: Built with high-quality birch plywood and finished with premium paint for enhanced durability and protection.
- LED Logo: A front-facing illuminated logo adds a modern, professional look, complementing any stage or venue setup.


The AK612 strikes a balance between performance, durability, and design, making it an ideal choice for sound professionals seeking reliability and quality.











TECHNICAL SPECIFICATIONS

12" 2-Way Bass reflex Passive Design

Speaker

500W RMS Power

Peak Power | 2000W

Freq. Response (-3dB) $58 Hz-20kHz(\pm 3dB)$

> 1x12" Ferrite LF driver/ 75mm VC **Drivers** 1x1" HF driver/ 44mm VC

97.5dB 1watt/1 metre Sensitivity

124dB SPL

Peak SPL 130dB

Impedance 8 ohms nominal 2×Speakon NL4 **Input Connectors**

Dispersion (HxV) 70x90

> Cabinet Premium Grade Birch Plywood with Black paint

Steel grille with anti-corrosion Front grille

coating

Colour Black $(W)300mm\times(D)370mm\times(H)533mm$ **Dimensions**

Net weight | 20kg