

# **KONTROL 1 PRO**





### **FEATURES**

- \* 30 Watts RMS Power Handling
- \* Professional Drivers and Crossover Network include Mounting Bracket
- \* Transparent and Faithful Sonic Performance
- \* Available In Black or White Finish
- \* Magnetically Shielded Transducers

System: Frequency Range (-10 dB) 95 Hz - 20 kHz Frequency Response (+/-3 dB) 100 Hz - 18 kHz **Power Capacity 30 W RMS** Sensitivity 88 dB SPL, 1W 1m (3.3 ft) Maximum SPL 100 dB **Nominal Impedance** 8 ohms **Crossover Frequency** 4.2 kHz

#### **Transducers:**

LF Driver 135 mm (5.25 in) low frequency Polypropylene Structural Foam loudspeaker **HF Driver** 

19 mm (.75 in) polycarbonate dome tweeter

Input Connectors Spring loaded terminals

#### **Enclosure:**

**Enclosure Material** Finish

Black

#### **Dimensions**

235 mm x 159 mm x 143 mm (9.3 in x 6.3 in x 5.6 in)

**Net Weight** 3.2 kg **Shipping Weight** 6 kg **Included Accessories** 

Mounting Bracket Assembly

## www.aeronsindia.com